WILDCAT PRODUCTS, INC.

2734 PEAR ORCHARD RD., GRANBURY, TEXAS 76048-7770


PHONE: (817) 579-7333 FAX: (817) 579-6646



APC - 30 FOAM CLEANER

APC-30 WAS DESIGNED TO LIFT STAINS AND SOIL UP OUT OF FELT. THIS WILL REPLACE THE TRADITIONAL METHOD OF BRUSHING BECAUSE BRUSHING JUST PUSHES THE DIRT INTO AND AROUND THE **APC-30** SURFACE OF THE FELT. IS A GENTLE NON-STAINING, FOAM CLEANER THAT LIFTS THE SOIL TO THE SURFACE ALLOWING YOU TO WIPE THE SURFACE CLEAN. SPRAY EVENLY OVER THE SURFACE AND WIPE WITH A CLEAN CLOTH. FOR VERY DIRTY SURFACES **ALLOW** APC-30 TO STAND MOMENTARILY BEFORE WIPING.

APC-30 COMES IN 18 OZ. AEROSOL CANS. 12 PER CASE



MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

This Web's Early lies with Control of the Control o						
	STRIBUTOR'S INFORMATION					
	HMIS Reling: Health-1; Flammability-1; Reactivity-0: Personal Protection-B					
Manufactured For:	DOT Hazard Classification: ORM-D					
Address:	Identity (trade name as used on label): $APC-32$					
Address:						
Phone:	MSDS Number: 170 Revision- 9					
Emergency Response Number:	Date Prepared: 02/24/93 Prepared By: ES/RC					
NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA Information Calls: (404)422-2071						
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES		CAS Number	SARA	OSHA PEL	ACGIH	Carcinogen
(Hazardous Components 1% or greater; Cardinogens 0.1% or greater)		1000 01 0	III LIST	(ppm)	TLV (ppm)	Rel. Source **
AMMONIUM HYDROXIDE		1336-21-6	No	35	25	g
ISOBUTANE		75-28-5	No	800	800	d
ETHYLENE GLYCOL MONOBUTYL ETHER		111-76-2	Yes	25	25	<u>d</u>
						<u> </u>
SECTION 2 - PHYSICAL /CH	EMIC	CAL CHARACTERIS	TICS	·		A
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS Boiling Point: N/A Specific Gravity (H2O=1): Concentrate Only = 1.0						
Vapor Pressure: PSIG @ 70°F (Aerosols): Max.60	Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A					
Vapor Density (Air = 1): N/E	Evaporation Rate (= 1): N/E					
Solubility in Water: Soluble	Water Reactive: No					
Appearance and Odor: White loam, mint tragrance.						
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA						
FLAMMABILITY as per USA FLAME PROJECTION TEST Auto Ignition Temperature Flammability Limits in Air by % in Volume:						
(aerosols) NON-FLAMMABLE N/E % LEL: N/E % UEL: N/E						
FLASH POINT AND METHOD USED (non-aerosols): N/A EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water.						
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.						
Unusual Fire & Explosion Hazards: Do not expose serosols to temperatures above 130°F or the container may rupture.						
SECTION 4 - REACTIVITY HAZARD DATA						
TABILITY X STABLE UNSTABLE HAZARDOUS POLYMERIZATION [] WILL X WILL NOT OCCUR						
ncompatibility (Mat. to avoid): Copper, alkali metals. Conditions to Avoid: Open flame, welding arcs, heat.						
Hazardous Decomposition Products: CO, CO2.						
SECTION 5 - HEALTH HAZARD DATA						
PRIMARY ROUTES OF ENTRY: [X] INHALATION [) INGESTION [X] SKIN ABSORPTION [] EYE [] NOT HAZARDOUS						
ACUTE EFFECTS						
Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.						
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.						
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture). May cause damage to hasal & respiratory passages, libroal & esophagus. Lab animals have experienced anemia, liver, kidney, jung, blood damage to Glycol Ether EB.						
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.						
EMERGENCY FIRST AID PROCEDURES						
Eye Contact: Flush with water for 15 minutes. If Irritated, seek medical attention.						
Skin Contact: Wash with soap and water. If Irritated, seek medical attention.						
Inhalation: Remove to Iresh air. Resuscitate if necessary. Get medical attention.						
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.						
SECTION 6 - CONTROL AND PROTECTIVE MEASURES						
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSR in positive pressure mode.						
Protective Gloves: Latex gloves recommended. Eye Protection: Safety glasses recommended.						
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.						
Other Protective Clothing & Equipment: None						
Hyglenic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.						
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE						
Steps To Be Taken If Material is Spilled Or Released: Dilute with water, absorb with suitable medium or neutralize with dilute acid & flush to sewer with water.						
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.						
Precautions To Be Taken in Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.						
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid lood contamination. Avoid breathing vapors.						
Other Precautions & or Special Hazaros: REEM OUT OF REACH OF CHILDREN. AVOID 1000 CONJUNIARIUM. AVOID ORBAINING VAPOIS.						